

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
18 March 2004 (18.03.2004)

PCT

(10) International Publication Number
WO 2004/023517 A1

(51) International Patent Classification⁷: **H01J 61/30**,
61/12, 61/82

(21) International Application Number:
PCT/IB2003/003807

(22) International Filing Date: 18 August 2003 (18.08.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
02078674.5 6 September 2002 (06.09.2002) EP

(71) Applicant (for all designated States except US): **KONINKLIJKE PHILIPS ELECTRONICS N.V.** [NL/NL];
Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **WIJENBERG**,

Christoffel [NL/NL]; c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). **HENDRICX, Josephus, C., M.** [NL/NL]; c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). **BORN, Matthias** [DE/DE]; c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).


(74) Agent: **DUSSELDORP, Jan, C.**; Philips Intellectual Property & Standards, Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),

[Continued on next page]

(54) Title: **MERCURY FREE METAL HALIDE LAMP**



(57) Abstract: A Hg-free metal halide lamp comprising a substantially cylindrical discharge vessel with a ceramic wall having an internal diameter D_i , an internal length L_i and a wall thickness W_t , and filled with an ionizable filling, wherein two electrodes are present having a mutual distance E_A for maintaining a discharge in the discharge vessel, wherein the filling comprises an inert gas and a salt, wherein the internal length L_i is smaller than 8 mm, wherein the electrode distance E_A and the internal diameter D_i comply with the relation $E_A/D_i > 2$, wherein the inert gas pressure P_{Xe} at room temperature is at least 5 bar, and wherein the wall thickness W_t and the internal diameter D_i comply with the relation $W_t/D_i > 0.15$.



Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,
SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM,
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

*patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG,
ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU,
TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE,
DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT,
RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM,
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)*

Declaration under Rule 4.17:

- *as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for the following designations AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW, ARIPO*

Published:

- *with international search report*
- *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Mercury free metal halide lamp

The invention relates to a Hg-free metal halide lamp comprising a substantially cylindrical discharge vessel with a ceramic wall having an internal diameter D_i , an internal length L_i and a wall thickness W_t , and filled with an ionizable filling, wherein two electrodes are present having a mutual distance EA for maintaining a discharge in the discharge vessel, wherein the filling comprises an inert gas, preferably Xe, and a metal halide.

Many automotive head lighting discharge lamp fillings to date contain mercury (Hg). Since mercury is known to be environmentally very unfriendly, many attempts were made to develop a mercury free metal halide lamp, but no satisfactory results have been obtained. Mercury in these lamps was mainly used to increase the electric field strength, whereby as a consequence the lamp current can be maintained at a low level, and the electronic ballast can therefore be simple and low cost. A suitable and satisfactory replacement for mercury had not yet been found. For general lighting purposes a solution is known where mercury is replaced by Zn or ZnI, but this solution is not suitable for the small automotive lamps, wherein the electrode distance EA is approximately 3 - 5 mm, and which usually have a power of between 20 and 35 W.

The invention aims at a suitable, efficient and reliable mercury free metal halide lamp for automotive headlight purposes.

After extensive development and testing, a combination of measurements has been found giving satisfactory results. According to the invention the internal length L_i of the discharge vessel is smaller than 8 mm, the electrode distance EA and the internal diameter D_i must comply with the relation $EA/D_i > 2$, the inert gas pressure P_{Xe} at room temperature should be at least 5 bar, and the wall thickness W_t and the internal diameter D_i must comply with the relation $W_t/D_i > 0.15$. It was found that the function of mercury in the lamp can at least partially be taken over by the high pressure of the inert gas, preferably xenon and an

extremely small vessel diameter. The discharge vessel must be as short as possible to obtain a sufficiently high coldest spot temperature. Hereby a sufficiently high lamp voltage of approximately 40 - 90 V can be obtained. The wall of the vessel must be sufficiently thick in order to prevent overheating of the wall and in order to prevent large temperature gradients inside the wall, which both can cause cracking, creep or even melting of the vessel.

Preferably the length of the cylindrical outer surface of the discharge vessel L_o is at least 8 mm, preferably at least 9 mm, more preferably at least 9.5 mm. Hereby a sufficient heat dissipation of the vessel is achieved.

For luminous efficacy the metal halide preferably comprises at least 40 :mol/cm³ of a rare earth iodide, such as NaPrI. Also preferably the metal halide comprises between 20 :mol/cm³ and 140 :mol/cm³ ZnI₂.

Preferably $L_i < 7.5$ mm, more preferably $L_i < 6.8$ mm, most preferably $L_i < 6.2$ mm. Preferably $EA/D_i > 3$, more preferably $EA/D_i > 4$. In practice EA/D_i will usually be smaller than 8, more usually smaller than 6. Preferably $Wt/D_i > 0.20$, more preferably $Wt/D_i > 0.25$, most preferably $Wt/D_i > 0.3$. Preferably $P_{Xe} > 10$ bar, more preferably $P_{Xe} > 15$ bar. In practice P_{Xe} will usually not be more than 25 bar.

In a preferred embodiment the discharge vessel is surrounded by a transparent substantially cylindrical gas filled outer bulb having its wall at a distance which is less than 1 mm, preferably less than 0.5 mm, for further improving the heat dissipation of, and heat distribution and homogenisation inside the wall of the discharge vessel. Also in a preferred embodiment the discharge vessel is provided with coated areas for increasing the coldest spot temperature.

The above and further aspects of the lamp according to the invention will now be explained by way of an exemplary embodiment and with reference to the drawings (not true to scale), in which:

Fig. 1 diagrammatically shows a lamp according to the invention; and

Fig. 2 shows the discharge vessel of the lamp of Fig. 1 in detail.

Fig. 1 shows a metal halide lamp provided with a discharge vessel 3. The discharge vessel 3 is shown in more detail in Fig. 2, with a ceramic wall 31 which encloses a discharge space 11 containing Xe and an ionizable filling. Two electrodes with tips 4a, 5a

having an interspacing EA are arranged in the discharge vessel 3, which has an internal diameter D_i at least at the area of the interspacing EA.

The discharge vessel is closed off at either end by a respective ceramic projecting plug 34, 35 which encloses with narrow interspacing a respective current lead-
5 through conductor 40, 50 to the electrode 4, 5 arranged in the discharge vessel. The discharge vessel is surrounded by an outer bulb 1. Part of the ceramic projecting plug 34, 35 and an adjoining portion of the ceramic discharge vessel 3 are provided with an external coating 41, 51. The lamp is further provided with a lamp cap 2. A discharge extends between the electrodes 4 and 5 in the operational state of the lamp. The electrode 4 is connected to a first
10 electrical contact forming part of the lamp cap 2 via a current conductor 8. The electrode 5 is connected to a second electrical contact forming part of the lamp cap 2 via current conductors 9 and 19. The current conductor 19 is surrounded by a ceramic tube 110.

The ionizable filling of the discharge vessel 3 of the lamp comprises 0.6 mg NaPrI and 0.1-0.2 mg ZnI₂. The filling further comprises Xe with a filling pressure at room
15 temperature of 16 bar.

The distance between the electrode tips EA is 5 mm, the internal diameter D_i is 1.2 mm, so that the ratio $EA/D_i=4.17$. The wall thickness W_t of the discharge vessel 3 is 0.4 mm. The internal length of the discharge vessel 3 L_i is 6.0 mm, the outer length L_o is 10 mm. The total length of the discharge vessel 3 and the plugs 34, 35 is 24.0 mm. The diameter
20 of the current lead-through conductors 40, 50 is 0.54 mm.

Part of the ceramic projecting plug 34, 35 and an adjoining portion of the ceramic discharge vessel 3 are provided with an external coating of Pt. The external coating extends to 0.25 mm from the relevant electrode tip. The outer bulb 1 of the lamp is made of quartz glass. The internal diameter of the outer bulb 1 is 3 mm, its wall thickness is 2 mm.
25 The outer bulb 1 is filled with N₂ with a filling pressure of 1.5 bar at room temperature.

The lamp has a power of 30 W, and a luminance of 78 Mcd/m². The maximum wall temperature is approximately 1700 K. The temperature gradient from the upper middle to the lower middle in a horizontally burning discharge vessel is less than 150 K.

CLAIMS:

1. A Hg-free metal halide lamp comprising a substantially cylindrical discharge vessel with a ceramic wall having an internal diameter D_i , an internal length L_i and a wall thickness W_t , and filled with an ionizable filling, wherein two electrodes are present having a mutual distance E_A for maintaining a discharge in the discharge vessel, wherein the filling
5 comprises an inert gas and a metal halide, wherein the internal length L_i is smaller than 8 mm, wherein the electrode distance E_A and the internal diameter D_i comply with the relation $E_A/D_i > 2$, wherein the inert gas pressure P_{Xe} at room temperature is at least 5 bar, and wherein the wall thickness W_t and the internal diameter D_i comply with the relation $W_t/D_i > 0.15$.

10

2. A lamp according to Claim 1, wherein the length of the cylindrical outer surface of the discharge vessel L_o is at least 8 mm, preferably at least 9 mm.

15

3. A lamp according to Claim 1 or 2, wherein the metal halide comprises at least 40 :mol/cm³ of a rare earth iodide.

4. A lamp according to Claim 1, 2 or 3, wherein the metal halide comprises between 20 :mol/cm³ and 140 :mol/cm³ ZnI₂.

20

5. A lamp according to any one of the previous Claims 1 - 4, wherein $L_i < 7.5$ mm, preferably $L_i < 6.8$ mm, more preferably $L_i < 6.2$ mm.

6. A lamp according to any one of the previous Claims 1 - 5, wherein $E_A/D_i > 3$, preferably $E_A/D_i > 4$.

25

7. A lamp according to any one of the previous Claims 1 - 6, wherein $P_{Xe} > 10$ bar, preferably $P_{Xe} > 15$ bar.

8. A lamp according to any one of the previous Claims 1 - 7, wherein $Wt/Di > 0.2$, preferably $Wt/Di > 0.25$, more preferably $Wt/Di > 0.3$.

5 9. A lamp according to any one of the previous Claims 1 - 8, wherein the discharge vessel is surrounded by a transparent substantially cylindrical gas filled outer bulb having its wall at a distance which is less than 1 mm, preferably less than 0.5 mm.

10. A lamp according to any one of the previous Claims 1 - 9, wherein the discharge vessel is provided with coated areas for increasing the coldest spot temperature.

1/2




FIG. 1

2/2




FIG. 2

INTERNATIONAL SEARCH REPORT

International Application No.
PCT/IB 03/03807

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 H01J61/30 H01J61/12 H01J61/82

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 H01J

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	DE 201 06 002 U (PATRA PATENT TREUHAND) 28 June 2001 (2001-06-28) page 4, line 22 - line 23 page 6, line 6 - line 9 figure 1	1-10
A	WO 97/42651 A (PHILIPS ELECTRONICS NV ; PHILIPS NORDEN AB (SE)) 13 November 1997 (1997-11-13) page 10, line 33 - page 11, line 16	1-10
A	US 6 404 129 B1 (MULLER HERMAN ET AL) 11 June 2002 (2002-06-11) column 4, line 18 - line 37; figure 2	1-10
	-/--	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- * & * document member of the same patent family

Date of the actual completion of the international search

28 January 2004

Date of mailing of the international search report

03/02/2004

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Zuccatti, S

INTERNATIONAL SEARCH REPORT

International A on No
PCT/IB 03/05807

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 2002/070668 A1 (LEVIS MAURICE E ET AL) 13 June 2002 (2002-06-13) paragraphs '0030!, '0082!, '0098!, '0101!; figure 2B -----	1-10
A	EP 1 063 681 A (STANLEY ELECTRIC CO LTD) 27 December 2000 (2000-12-27) page 4, line 27 - line 28 -----	1-10

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/IB 03/03807

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
DE 20106002	U	28-06-2001	DE 10026802 A1	03-01-2002
			DE 20106002 U1	28-06-2001
			BE 1014199 A6	03-06-2003
			CA 2349082 A1	30-11-2001
			CN 2539286 U	05-03-2003
			FR 2809865 A3	07-12-2001
			GB 2366908 A	20-03-2002
			US 2002008476 A1	24-01-2002
<hr/>				
WO 9742651	A	13-11-1997	US 5828185 A	27-10-1998
			US 6111359 A	29-08-2000
			CA 2226467 A1	13-11-1997
			CN 1193413 A , B	16-09-1998
			EP 0838082 A2	29-04-1998
			WO 9742651 A2	13-11-1997
			JP 11509680 T	24-08-1999
			US 5998939 A	07-12-1999
<hr/>				
US 6404129	B1	11-06-2002	CN 1302448 T	04-07-2001
			WO 0067294 A1	09-11-2000
			EP 1092231 A1	18-04-2001
			JP 2002543576 T	17-12-2002
<hr/>				
US 2002070668	A1	13-06-2002	US 2003034736 A1	20-02-2003
			US 6414436 B1	02-07-2002
			US 2003052609 A1	20-03-2003
			WO 03030212 A1	10-04-2003
<hr/>				
EP 1063681	A	27-12-2000	JP 2001006610 A	12-01-2001
			EP 1063681 A2	27-12-2000
<hr/>				